

# GasAlert LEL

## Combustible Gas and Vapors

"INNOVATORS IN GAS DETECTION"

# BW

Technologies



### Combustible Gas Detector 0-100% LEL



ACTUAL SIZE

### Protect Yourself

- ▲ Continuous LCD shows real-time gas concentration with backlight in low light (auto); in alarm (auto) and on demand
- ▲ Compact (1.5 x 2.0 x 3.75 in / 38.5 x 50 x 95 mm) and lightweight (4.6 oz. /131 g)
- ▲ Provides 90 dB tone and bright LED indication on alarm (typical)
- ▲ Available with internal vibrating alarm
- ▲ Simple, automatic calibration procedure
- ▲ Peak value displayed on command in % LEL
- ▲ LOW and HIGH alarms with adjustable setpoints
- ▲ Over Limit alarm and sensor protection
- ▲ User field options include: Pass Code Protection, Latching High Alarm and Confidence Beep
- ▲ Equipped with a plug-in replaceable sensor
- ▲ Powered by a integral rechargeable lithium ion battery
- ▲ Intrinsically safe to U.S., European and Canadian standards
- ▲ Full function self-test of: sensor, battery and circuitry integrity; and audible/visual alarms
- ▲ Pocket/belt clip, test cap and hose, battery, charger and instructions in local languages included



### NEW 5-Port Multi-Charger

### Ordering Information

#### GasAlert LEL Detectors

- GA-W\* GasAlert LEL 0-100% LEL detector
- GAA-W\* GasAlert LEL detector with internal vibrator alarm

#### GasAlert LEL SamplerPak

- Includes GasAlert LEL detector with Sampler motorized pump, 10 ft. / 3 m sampling hose and two sampling tubes in a carrying case.
- GA(A)-W-SK\* GasAlert LEL SamplerPak
- GA(A)-W-SKC\* GasAlert LEL SamplerPak with charger/battery kit

#### Accessories and Spares

- GA-TS03 GasAlert LEL automatic test station
- GA-HC-1 Hard hat clip
- GA-AG-1 Alligator clip (non-conductive ABS)
- GA-AG-2 Alligator clip (stainless steel)
- GA-BALERT2 Concussion-proof boot
- GA-NS-1 Neckstrap
- CG2-J-2.5-34 Methane calibration gas cylinder (34 L)
- CG2-R-1.0-34 Propane calibration gas cylinder (34 L)
- CG2-K-0.75-34 Pentane calibration gas cylinder (34 L)
- D4-E2358 Earphone
- GA-SS Sensor screens
- GA-WBAT Replacement battery
- GA-TC-1 Test cap and hose
- GA-W-CD1 Training CD
- GA-C02 Single charger with 110 VAC main plug\*
- GA-C02-MC5 Multi-unit charger with 110 VAC main plug\*

\*Note: Add suffix for delivery with 220 VAC charger:  
 Europe: -EU United Kingdom: -UK Australia: -AU

[www.gasmonitors.com](http://www.gasmonitors.com)

Email: [info@bwt.net](mailto:info@bwt.net)



# GasAlert LEL

0-100% LEL

## Single-Gas Detector

GasAlert LEL provides extraordinary cost of ownership advantages, including automated calibration and simple push-button controls. Both of these features lowers your training and maintenance costs. GasAlert LEL is operated by an advanced microcontroller and is equipped with a plug-in, poison resistant catalytic bead sensor and high output audible/visual alarms.

The Over Limit alarm is latching and must be acknowledged by the user to shut it OFF. User field options include Pass Code Protection, Latching High Alarm and Confidence Beep.

The bright, large LCD shows real-time gas concentrations and the instrument's status at all times. The full function self-test verifies sensor, circuitry and battery integrity and activates the audible/visual alarms each time you turn the instrument on. The detector clearly advises the gas hazard present—Low and High gas alarms. Recorded Peak exposures can be displayed on demand.

The compact, rugged GasAlert LEL is designed with the most advanced RFI protection available today. Delivered ready for use, simply clip the instrument to your pocket or belt for unequalled protection.

"INNOVATORS IN GAS DETECTION"



### For further information:

1-888-749-8878 USA  
 1-800-663-4164 Canada  
 +44 (0) 1869 233004 Europe  
 +971-4-8871766 Middle East  
 +61-7-3818-8244 Australia  
 +852-2974-1783 China  
 +1-403-248-9226 Other Countries

### Corporate Headquarters

2840 - 2 Avenue S.E.  
 Calgary, AB, Canada T2A 7X9  
 Phone: +1-403-248-9226  
 Fax: +1-403-273-3708

E-mail: info@bwt.net.com  
 www.gasmonitors.com

BW1005-01-01-00-8.25x11-20040304-5006-5

## SPECIFICATIONS

DETECTOR: Single-gas detector

GasAlert LEL:	Measuring Range	Alarms		
		Low Level	High Level	Over Range
Combustible Gases/Vapors:	0-100%LEL	10% LEL	20% LEL	100% LEL

<sup>1</sup>Factory defaults are shown. Alarm levels are field adjustable.

Auto zero: Yes  
 Calibration: Automatic  
 Backlight: Low light (auto); alarm condition (auto); on demand  
 Full function self-test: Verifies integrity of sensor, circuitry and battery; audible/visual alarms  
 Sensor: Catalytic bead. Poison resistant (equipped with filters to eliminate the poisoning effects of silicone vapors and sulfur compounds).

**INDICATORS AND ALARMS:** Clearly advises alarm levels both visually and audibly  
 Visual alarm: Wide-angled alarm lens, plus alarm LCD readout  
 Audible alarm: High-output, pulsing 90 dB at 1 ft. / 0.3 m (typical)  
 Over limit alarm: Latching alarm at 100% LEL  
 User field options: Pass Code Protection, Latching High Alarm and Confidence Beep  
 Confidence beep: Every 5 seconds (field-selectable)  
 Other: Low battery; off warning; sensor fail  
 Optional internal vibrator: Vibrates in sync with audible and visual alarms

**CONTINUOUS LCD DISPLAY:** Alphanumeric gas readout and status display advises:  
 Gas %: Continuously displays gas concentration present  
 Peak %: Records and displays peak (maximum) exposure to gas on demand  
 Setpoints: Displayed on activation (auto) and on demand in %

**TESTS:**  
 Full function self-test: Full function self-test on activation (auto)  
 Battery: Continuous (auto)

**GENERAL SPECIFICATIONS:**  
 Shock-resistant ABS enclosure  
 Operating temperature: -20 to +45 °C / -4 to +114 °F  
 Humidity: 5% to 95% RH (non-condensing)  
 EMI/RFI: Complies with EMC Directive 89/336/EEC  
 Battery Type: Rechargeable integral lithium ion  
 Battery Life: Up to 14 hours per charge; 500 to 600 charges  
 Size: 1.5 x 2.0 x 3.75 inches / 38.5 x 50 x 95 mm  
 Weight: 4.3 oz. / 131 g

**WARRANTY:** 2 years including sensor

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

**RATINGS AND CERTIFICATIONS:**  
 (Intrinsic safety)

CLASSIFIED: Class I, Div. 1, Gr. A, B, C, D  
 BAM: 03 ATEX 0001 x

**ATEX:** CE II 2 G  
 EEx ia d IIC

CE: European Conformity  
 T-Code: N.A. T3C  
 Europe T4



- 1 LARGE, ALPHANUMERIC DISPLAY
- 2 ADVANCED MICROCONTROLLER-BASED OPERATION
- 3 CATALYTIC SENSOR
- 4 BRIGHT, WIDE-ANGLED VISUAL ALARM LENS
- 5 HIGH-OUTPUT 90 dB AUDIBLE ALARM
- 6 AUTO ZERO, AUTO CALIBRATION
- 7 AUTO BACKLIGHT
- 8 LOW, HIGH AND OVER RANGE ALARMS
- 9 ALARM ACKNOWLEDGE FEATURE
- 10 RUGGED, COMPACT, LIGHTWEIGHT


Full Information STATUS Panel with easy prompts:



△ Advises Alarm Level encountered (LOW/HIGH)



△ Auto zero and easy prompted calibration



△ Records and displays Peak (Max) exposure



△ LOW battery

Locally distributed by:

